

IMPACT 400 Series

- Dual-microphone system with advanced filtering algorithms ensures clear calls
- Tuned speakers deliver crisp, professional audio so you never miss a word
- Soft ear pads, light build, and padded headband keep you comfortable all day

Outer master carton Stereo version

- Plug-and-play setup and lift-to-mute make daily use smooth and intuitive
- Certified for Microsoft Teams Open Office, great performance at a competitive price point

Design	Wearing style	Headband; Stereo and Mono variants	
	Ear coupling	On-ear	
	Ear pad material	Leatherette	
	Length of boom arm	14 cm 5.5 in	
	Color	Black	
Smart features	LED features and functions	Call control on headset, Backlit Teams button, Busy light, Mute LED in boom arm	
	Boom arm	Flexible, 270 degrees rotation for left and right wearing, lift to mute	
Connectivity	Interface	USB-C & USB-A (USB-C to A adapter included)	
•	Power via USB cable	5V 100mA	
Microphone	Acoustical principle	Noise cancelling	
	Environmental noise cancellation (ENC)	Al based noise reduction	
	Number of microphones		
	Microphones for voice pick-up		
	Microphone technology	Electret condenser	
	Microphone pick-up pattern	Uni-directional	
	Frequency repsonse	100 Hz - 8 kHz Wideband	
	Sensitivity	-22 dBFS/Pa	
Speaker	Acoustical principle	Dynamic closed	
	Bandwidth (speak mode)	100 Hz - 8 kHz Wideband	
	Bandwidth (music mode)	20 Hz - 20 kHz	
	Sensitivity	110 +/- 3 dB @ 1 kHz, 1 mW	
	Max sound pressure	96 dB SPL @ 1 kHz	
	Total harmonic distortion	< 3 % @ 1 kHz	
	Impedance	32 ohm	
	Size	32 mm	
	User hearing protection	EPOS ActiveGard®, EU Noise at Work limiter	
Weight	Headset weight	Double-sided: 124 g 4.4 oz Single-sided: 103.6 g 3.6 oz	
	Single packaging Stereo version	376 g 13.26 oz	

4560 g | 160.85 oz

Dimensions	USB-C cable length	200 cm 78.74 in	
	Mono headset (LxWxH)	62 x 172 x 167 mm 2.44 x 6.77 x 6.57 in	
	Stereo headset (LxWxH)	62 x 172 x 167 mm 2.44 x 6.77 x 6.57 in	
	Earcups (D)	62 mm 2.44 in	
	Single packaging (LxWxH)	200 x 201 x 63 mm 7.87 x 7.91 x 2.48 in	
	Outer master carton (LxWxH)	420 x 320 x 245 mm 16.53 x 12.60 x 9.64 in	
Software & Apps	EPOS devices can be managed with following Software solutions:		
	EPOS Connect	Conduct firmware updates and configure headsets for personal audio preferences: eposaudio.com/software-epos-connect	
	EPOS Connect desktop app	EPOS Connect freeware for Windows and Mac.	
	EPOS Connect browser	A web-based solution for updating the firmware of your EPOS devices	
	EPOS Manager	Manage, update and configure EPOS audio devices from any location. For both cloud and on-premises solutions: eposaudio.com/software-epos-manager	
	Supported Operating systems	Windows, MacOs, DellWyse, Linux, Stratodesk, IGEL, eLux, Chrome OS	
Extended info	Warranty	2 years	
	Operating temperature	-10°C to 50°C 14°F to 122°F	
	Storage temperature	-10°C to 60°C 14°F to 140°F	

Product information

Product	What's in the box	Certifications and compliance	EAN code	UPC code
IMPACT 460 Art. no. 1001251	Double-sided headset, USB-C to USB-A adapter, Carry pouch, Quick guide, Safety guide and Compliance sheet	Certified for Zoom, Google Meet, Google Voice, Works With Chromebook	57 1470801060 9	840064412681
IMPACT 460T Art. no. 1001253	Double-sided headset, USB-C to USB-A adapter, Carry pouch, Quick guide, Safety guide and Compliance sheet	Certified for Microsoft Teams	57 1470801062 3	840064412681
IMPACT 430 Art. no. 1001252	Single-sided headset, USB-C to USB-A adapter, Carry pouch, Quick guide, Safety guide and Compliance sheet	Certified for Zoom, Google Meet, Google Voice, Works With Chromebook	57 1470801061 6	840064412377
IMPACT 430T Art. no. 1001254	Single-sided headset, USB-C to USB-A adapter, Carry pouch, Quick guide, Safety guide and Compliance sheet	Certified for Microsoft Teams	57 1470801063 0	840064412384

Spare parts

Product	Short Description	EAN code	UPC code
IMPACT 400 Ear pads Art. no. 1001387	Leatherette ear pads - 2 pcs	57 1470801217 7	8 4006441197 4
Replacement USB-C to USB-A Adapter Art. no. 1001474	USB-C to USB-A Adapter	57 1470801295 5	8 4006441274 2

See more at eposaudio.com

Technical specifications